



Intel® System Firmware Update Utility

User Guide – For Intel® Server System M70KLP

Reference for using the Intel® System Firmware Update Utility (Sysfwupdt)

Rev 1.00

March 2021

Delivering Breakthrough Datacenter System Innovation – Experience What’s Inside!

<Blank page>

Document Revision History

Date	Revision	Changes
March 2021	1.00	First version for Server System M70KLP platform

Disclaimers

Intel technologies' features and benefits depend on system configuration and may require enabled hardware, software, or service activation. Learn more at Intel.com, or from the OEM or retailer.

You may not use or facilitate the use of this document in connection with any infringement or other legal analysis concerning Intel products described herein. You agree to grant Intel a non-exclusive, royalty-free license to any patent claim thereafter drafted which includes subject matter disclosed herein.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document.

The products described may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Intel disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade.

Copies of documents which have an order number and are referenced in this document may be obtained by calling 1-800-548-4725 or by visiting www.intel.com/design/literature.htm.

Intel and the Intel logo are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

*Other names and brands may be claimed as the property of others.

© Intel Corporation

Table of Contents

1. Introduction	7
1.1 Purpose of the document	7
1.2 Platforms and OS support	7
1.3 Intended audience	7
1.4 Order of precedence	7
1.5 Document overview	7
2. Product overview	9
2.1 Overview	9
2.2 Features	9
2.3 Update Process Overview	9
2.3.1 Flash/Firmware Update Operation	9
3. Functional specification	11
3.1 Command-line interface	11
3.1.1 Update system BIOS and Firmware	12
3.1.2 Display version information	12
3.1.3 Modify specified FRU field through command line	12
3.1.4 Displays Given Area of FRUSDR and SMBIOS	13
3.1.5 Restore BIOS Defaults	13
4. Installation and Un-installation	14
4.1 Windows* Installation	14
4.1.1 Installation	14
4.1.2 Uninstallation	14
4.2 Linux* Installation	14
4.2.1 Installation	14
4.2.2 Uninstall	15
4.3 UEFI Installation	15
4.3.1 Installation	15
4.3.2 Uninstall	15
Appendix A. Exit Error Codes	16
Appendix B. Glossary	17

List of Tables

Table 1: Command Line Switches	11
Table 2: Exit Error Codes.....	16

1. Introduction

1.1 Purpose of the Document

This document describes the functionality of the Intel® System Firmware Update utility, also referred to “sysfwupdt”. Based on this document, users can get to know how this utility works.

1.2 Platforms and Operating System Support

This utility is designed exclusively for use with Intel® Server System M70KLP. Using this revision of the utility on any other Intel® server product is not supported. For details, refer to Release Notes in each release package.

There are two ways to identify the M70KLP version of the utility:

- Check the utility zip pkg name string
The M70KLP Utility zip pkg string contains ‘**klp**’ keyword.
Ex:
Sysfwupdt_V14_2**klp**_Buildx_AlLOS.zip
- Check the utility header after launching the tool
The M70KLP utility header contains the ‘**klp**’ keyword. Check the header string after launching the tool.
Ex:

```
[root@localhost linux_rh8_for_secureboot]# sysfwupdt -h

System Firmware Update Utility Version 14.2klp Build 4
Copyright (c) 2021 Intel Corporation

Usage: sysfwupdt [-h] [-u [-kcs] {path of update files} {update options}] [-i] [-cfg] [-fru] [-sdr]
```

Figure 1. M70KLP Utility Header

1.3 Intended Audience

This document is intended for:

- Developers of BIOS and Baseboard Management Controller (BMC) FW and their respective validation team engineers
- System Level Validators
- Users of the utility who desire a more detailed understanding of its operation.

1.4 Order of Precedence

In case of conflict between different documents, the current document shall take precedence over the other documents.

1.5 Document Overview

This document contains information pertaining to the System Firmware Update utility. This document is organized as follows:

Section 1: Introduction

This section describes the purpose of the document.

Section 2: Product Overview

This section provides an overview of the architectural components that make this utility.

Section 3: Functional Specification

This section describes the operation, how to use this utility, and a description of the input files used by this utility.

Section 4: Installation and Un-installation

Section 5: Exit Error Codes

This section describes the error code of the application. It also describes what each exit code means.

2. Product Overview

2.1 Overview

The System Firmware Update utility provides the ability to update the system BIOS and Firmware while the server is running its host operating system. This utility is a command-line tool and it requires users to have admin (Windows*) or root (Linux*) privileges.

This version of the System Configuration Utility is designed for use only with the Intel Server System M70KLP product family. When using the System Configuration Utility for other Intel® server product families, check the product family documentation for the applicable System Configuration Utility version.

2.2 Features

The Sysfwupd utility supports following features:

- BIOS Update – Update PFR BIOS in the system, tool transfer the bin file to BMC and the real update will start on next reboot by default.
- BMC Update - Update Server Management (SM) firmware (FW) of the Baseboard Management Controller (BMC), and on next BMC reset the new BMC FW will be loaded.
- CPLD Update
- NVRAM Update
- Recovery Update
- Modify specific FRU field
- Display BIOS/ME/BMC/Base Board/System/FRU / SDR / SMBIOS information
- Restore BIOS Default setting

Below features are not supported currently:

- FRUSDR Update – update the Field Replaceable Units (FRU) in Non-Volatile RAM and Sensor Data Records of the system in BMC staging area.

2.3 Update Process Overview

This section contains an overview of the update process. A full description of the internal mechanism in the BIOS, Firmware, and Hardware is outside the scope of this document. Refer to the *FW / BIOS EPS* for a complete description.

The front panel of the server is locked during the update of any of the components to prevent the user from accidentally triggering a reset or power down. The Ctrl-C and Ctrl-Break keys are also disabled while running this utility.

Note: The front panel locking feature is not supported on BMC-less platforms.

2.3.1 Flash/Firmware Update Operation

This section describes the update process of the BIOS and Firmware.

The Utility passes the image file to the BMC by using IPMI commands. The BMC receives and validates the image data. The BMC only programs image data to “staging area” and inform CPLD with corresponding options after the data in staging area is ready. The real update from staging area to active region will be done by the CPLD in next T-1.

By default, real update process will not be started until the user manually reboots the system. The behavior can be changed by adding ImmReset option in the command line, which will allow system reset automatically.

Refer to BIOS and BMC EPS for more details.

3. Functional Specification

The executable for the System Firmware Update utility is named **sysfwupdt.exe** for Windows*, **sysfwupdt** for Linux* and **sysfwupdt.efi** for UEFI shell.

3.1 Command-line Interface

This utility parses the command-line arguments and sets internal flags to control operation. Any invalid parameters will result in a “usage” message being displayed and the program exiting with an error code (see Table 2).

The command line switches are listed in Table 1 and they are accessed with a dash “-” or a slash “/”.

The basic command line format is:

```
sysfwupdt [Options]
```

Table 1: Command Line Switches

Parameter	Description
sysfwupdt	The name of the utility. Linux* is case sensitive.
[FileName]	Name of the binary file used for the update. The file path can be specified with the file name. There is no default file name or file extension. Either the “/u” or the “/i” option must always precede the FileName.
[Update Option]	Optional BIOS update option such as “ImmReset”, “UpdateNvram”, Multiple strings should be concatenated with + character like “UpdateNvram+ImmReset”. Update Option should be at the end of command line. For detailed BIOS update options, refer to BIOS release.
-h or -?	Displays command line help information. When this option is used, any other options on the command line are ignored. When using /? In Linux* enclose within double quotes (“/?”)
-i	This option displays BIOS/ME/BMC/CPLD/BaseBoard information in the system. If binary files are specified with this option, this option will display the corresponding version in binary files. This option is not valid with any other options. The syntax is: sysfwupdt -i <FileName> sysfwupdt -i
-kcs	Transfer data by kcs interface. This should be used in conjunction with -u <bmc cpld> Note: this is not valid in case of -u <bios>
-recovery	This option update firmware to the recovery area as well. This should be used in conjunction with the -u.
-u	Update system BIOS/BMC/CPLD. At least one binary file name must be specified with this option. An Update Option is optional. The syntax is: sysfwupdt -u [FileName] Sysfwupdt -u [FileName] <Update Option>
-d	Display FRU/SDR/SMBIOS information The syntax is: sysfwupdt -d [fru sdr smb]
-set	Set different FRU area as below sysfwupdt /set “area name” “FRUFIELD” “value” Where area name can be “product”, “chassis” and “board” depending on the FRU area to be modified.
-rd	Restore bios default settings Sysfwupdt /rd “” A system reboot should be performed after -rd command

3.1.1 Update System BIOS and Firmware

The following command updates the BIOS and Firmware from the bin files. Both single and multiple input files are supported. Following the update, user must manually reset the system before the update will take effect in case there is no `ImmReset` specified in command line.

```
sysfwupd -u BIOSfilename BMCfilename CPLDfilename
```

With `/kcs`, user could choose KCS method to do an update.

To do recovery BIOS/BMC update:

```
sysfwupd -u [File Name] -recovery
```

To force update Nvram region:

```
Sysfwupd -u [File Name] UpdateNvram
```

To set immediate restart and force update Nvram region:

```
Sysfwupd -u [File Name] UpdateNvram+ImmReset
```

Note: No option is allowed to be inserted between `-u` and `"[File Name]"`. And multiple update option strings can be concatenated with `+` character.

3.1.2 Display Version Information

The following command displays the BIOS/ME/BMC/SDR /BaseBoard information of the system.

```
Sysfwupd -i
```

To display the BIOS/BMC file version:

```
Sysfwupd -i [BIOSfilename|BMCfilename]
```

3.1.3 Modify Specified FRU Field Through Command Line

This command is to modify the FRU fields of chassis and product area without using a CFG file.

```
Sysfwupd-set "area name" "FRUFIELD" "value"
```

Where area name can be `"product"`, `"chassis"` or `"board"` depending on the FRU area to be modified. The following are the frufield parameters:

"CT", "Chassis Type"

"MN", "Manufacturer Name"

"PN", "Product Name"

"P#", "Part Number"

"S#", "Serial Number"

"PV", "Product Version"

"AT", "Asset Tag"

"ID", "Manufacturer ID"

"MD", "Manufacturer Date & Time"

"AMx", "Additional Manufacturer Field"

Note: For the chassis area, the fields "At", "Pn" and over are not supported. For the board area, only "Pn" field is supported

3.1.4 Displays Given Area of FRUSDR and SMBIOS

This command will display the indicated area given by argument. If the given display function fails because of an inability to parse the data present or hardware failure the utility will display an error message. For example, if the sensor data record area is empty, the utility will display an error message saying, "No Sensor Data Records found on the server".

```
Sysfwupdt /d [FRU|SDR|SMB]
```

3.1.5 Restore BIOS Defaults

Following Command will restore the BIOS default settings.

```
Sysfwupdt -rd ""
```

4. Installation and Un-installation

4.1 Windows* Installation

4.1.1 Installation

The System Firmware Update utility can be installed on Windows* using the following method:

1. Unzip zip package and copy the contents to external media.
2. Connect the external media to SUT (System Under Test).
3. Go to the Drivers\Win folder, choose x86 or x64 (depending on the operating system).
4. Run install.cmd to install the drivers.
5. Go to win_x86 or win_x64 folder.
6. Now run sysfwupdt.exe.

4.1.2 Uninstallation

1. Run uninstall.cmd to uninstall all the drivers.
2. Remove the sysfwupdt folder structure.
3. Reboot the system for the changes to take effect.

4.2 Linux* Installation

Refer to the supported operation system listed in Release Notes.

4.2.1 Installation

4.2.1.1 RPM Installation

1. Copy `sysfwupdt rpm` from corresponding folder to local folder.
 - > for RHEL older than 8.0, copy from Linux_x64\RHEL
 - > for RHEL8.0 and above, copy from Linux_x64\RHEL\RHEL8
 - > for SLES older than 15, copy from Linux_x64\SLES
 - > for SLES15 and above, copy from Linux_x64\SLES\SLES15
2. If there another version has already been installed, uninstall that version first before installing the new version.
3. Install `sysfwupdt` utility by using "`rpm -ivh sysfwupdtxx.rpm`". This will install the utility in "`/usr/bin/sysfwupdt/`".
4. On RHEL/SLES after installing the rpm, close the terminal from which rpm was installed and then execute utility from a new terminal.

4.2.1.2 Regular Installation:

1. Copy the zip package (for RHEL or SLES) to local folder.
2. Unzip to local folder (example: `.\sysfwupdt`). Go to `sysfwupdt` folder (`cd sysfwupdt`).
3. `# chmod 755 install.sh`
4. Install the utility using the command: "`#!/install.sh`"
5. Go to the RHEL or SLES directory (based on operating systems)
6. Unzip the file `sysfwupdt.zip` to get `sysfwupdt` executable for Linux* OS
7. Now you can run command with options (example: "`#!/sysfwupdt -i`")

4.2.2 Uninstall

To uninstall the sysfwupdt utility, remove the sysfwupdt folder structure.

For RPM uninstallation, run command `#rpm -e sysfwupdt` for RPM uninstallation

4.3 UEFI Installation

Refer to the supported operation system listed in Release Notes.

4.3.1 Installation

The System Firmware Update utility can be installed on UEFI using the following method:

1. Unzip the package and copy the contents to external media.
2. Connect the external media to SUT (System Under Test)
3. Go to UEFI_x64 folder.
4. Now run sysfwupdt.efi.

4.3.2 Uninstall

To uninstall the sysfwupdt utility, remove the sysfwupdt folder structure.

Appendix A. Exit Error Codes

The following error codes are useful when executing the System Firmware Update utility from a script. The error messages displayed provide more information as to the cause of the error.

The `ERRORLEVEL` command in the configuration file overrides the error codes described in this Table 2. The `ERRORLEVEL` command, described in the Configuration File Format EPS, causes the utility to exit immediately and return the error code specified.

Table 2: Exit Error Codes

Value	Interpretation	Suggested Actions
0	Successful termination.	
1	Invalid invocation or unknown command line argument.	Check whether the command line arguments are correct. Refer to Table 1: Command Line Switches for valid command line arguments.
2	File was not found.	Check whether files are present there. If not, place the files in the proper location and execute.
3	Unable to read a file.	Unable to read file.
4	File is mismatched with the target system.	Check whether the files used for the update belong to the target platform. If not, provide the files compatible with the target system.
5	File is invalid or its format is not supported by this version of the utility.	Check whether the file is corrupt or has an invalid format / file extension. If corrupt, then use proper files.
6	BIOS interface failed – this error can occur while reading / writing to BIOS.	Check whether the SMBIOS is populated correctly.
7	FW interface failed – this error can occur when reading or writing to the BMC, setting the update notification, or updating any of the FW components (BMC, FRU, SDR).	Check whether the BMC hardware is functioning properly. Check whether the BMC/SDR versions are displayed correctly in the BIOS setup. If not, contact the hardware vendor.
8	User has no Admin or root rights.	Check whether the user logged in has root/administrator privilege. If not, log in as administrator or root.
9	Utility is already running in another process.	Check whether another instance of the utility is already running. If running, wait for the instance to finish and then start again.
10	Memory allocate failed.	Memory Allocation Failed. Investigation required.
11	Password mismatched.	Admin password provided by user is mismatched to current system admin password.
11	Failed to access IO port.	Check UEFI secure boot status and ensure UEFI secure boot is disabled in BIOS F2 menu. If utility runs on Debian and SLES* 15 OS, user needs to add "iomem=relaxed" to grub boot option to enable IO memory map.

Appendix B. Glossary

Term	Definition
BCD	Binary Coded Decimal
BIOS	Basic Input Output System
BMC	Baseboard Management Controller. The primary microcontroller that controls the operation of the Intel® server management subsystem.
CFG	Configuration (file).
CHAFF2L	Copy HTTP And FTP Files To Local – program used by the One-Boot Flash Update utility to download files from http and ftp servers.
EAS	External Architecture Specification
EPS	External Product Specification
FRU	Field Replaceable Unit
FUD	Flash Update Driver
FW	Firmware
HW	Hardware
IA	Intel® Architecture
ID	Identification
IMB	Intelligent Management Bus
IPS	Internal Product Specification
IPMB	Intelligent Platform Management Bus. Name for the architecture, protocol, and implementation of a special bus that interconnects the baseboard and chassis electronics and provides a communications media for system platform management information.
IPMI	Intelligent Platform Management Interface
LCD	Local Control Display
ME	Management Engine
OEM	Original Equipment Manufacturer
Op Code	Operational Code
PIA	Platform Information Area
POST	Power On Self Test
RMM3	Remote Management Module
RPM	Red Hat Package Manager
SDR	Sensor Data Record
SEL	System Event Log
SM	Server Management
SMS	Server Management Software
URL	Universal Resource Locator